



ITEM 項目	PARTS NAME 零件名稱	MATERIAL 材質	
1	I/O CONNECTOR	HOUSING:LCP	Black
		CONTACT:BRASS	15u"Gold
		SPRING:SUS304	----
2	COVER TAPE	polystyrenes	(COLOR:TRANSPARENT)
3	REEL	polystyrenes	(COLOR:TRANSPARENT)
4	CARRIER TAPE	polystyrenes	700PCS/CARRIER
5	WATERPROOF BAG	POLYETHYLENE	-
6	LABEL	-	-
7	BOX	CORRUGATED (DOUBLE WALL)	12PCS CARRIER/BOX 8400 PCS CONNECTOR/BOX

SPECIFICATION
MATERIAL
See drawing
STANDARD DATA
Operating temperature: -30°C ~ +70°C
Storage temperature: -40°C ~ +85°C
ELECTRICAL
Insulator resistance: 100M ohms Min. @ 500 VDC
Withstanding voltage: 500 VDC / minute
Contact resistance: 50 m ohms Max.
MECHANICAL
Spring force: See drawing
Durability: 20000 cycles Min.
PART NO.

SERIES B 7 3 - 0741 - 03 001
MODEL NO. TYPE NO.
B=Twin charger 01=Type 1
PRODUCT TYPE POGOPIN NUMBER
7=Machine pin type 03=3 position
CONTACT TYPE 3=SMT type



WALTA 華大電子股份有限公司
WALTA ELECTRONIC CO.,LTD.
TEL:886-2-27565688;FAX:886-2-27673342

REV. 版本	ECN NO. 設變號碼	MARK 記號	REVISIONS 設變內容	SIGN 修改	DATE 日期	UNLESS OTHERWISE SPECIFIED TOLERANCE 尺寸公差	CHECKED 審核	DESIGNED 設計	TITLE 產品名稱	UNIT 單位	SCALE 比例	SIZE 尺寸	PART NO. 產品料號	DOC. NO. 文件編號	REV. 版本
A	E0807-022	X 0	新開	-	-	X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±5'00"	APPROVED 承認	HUABO 31/08/08"	POGO PIN CONNECTOR	MM	5/1	A3	B73-0741-03001	CUT-0741-001	1/2 A