

E-marker 燒錄信息：

Device Parameters	
Parameters	Value
Part number	CYPD2103-20FNXI
Flashing VID<0x>	04B4
Flashing mode index	1
USB Vendor ID<0x>	522
USB Product ID<0x>	A18
Config table major version	0
PD revision	3.0

Firmware	
Parameters	Value
Part number	CYPD2103-20FNXI
Device family	CCG2
Application type	CABLE
Running mode	Main FW
Bootloader	
Base version	1.0.0.642
App version	0.0
Failsafe firmware	
Base version	1.0.3.898
App version	1.5
Main firmware	
Base version	1.0.3.898
App version	1.5
Programmable	Yes

Device IDs	
Parameters	Value
USB host support	No
USB device support	No
Modal operation supported	Yes
USB Vendor ID<0x>	522
Product type<Cable>	Passive Cable
Connector Type	Reserved for compatibility with legacy
USB-IF compliance XID<0x>	944
USB Product ID<0x>	A18
Bcd device<0x>	190

Cable VDO	
Parameters	Value
Cable hardware version<0x>	1
Cable firmware version<0x>	1
Cable type	Type-C to Type-C
EPR mode capable	Yes
Cable latency	Less than 10ns
Cable termination type	VCONN not required
Maximum Vbus voltage<V>	5.0
VBus current handling capability	5A
Sop"controller present	No
USB version	[USB4]Gen3

SVID 0	
SVID Value<0x>:4B4	
Parameters	Value
Mode 0 <0x>	1

SVID 1	
SVID Value<0x>:8087	
Parameters	Value
Mode 0 <0x>	30001



華大電子股份有限公司
WALTA ELECTRONIC CO.,LTD.
TEL:886-2-26577778;FAX:886-2-26575659

						UNLESS OTHERWISE SPECIFIED TOLERANCE 尺寸公差	CHECKED 審核	DESIGNED 設計 zhijun 2024/12/18	 TITLE 產品名稱 Thunderbolt 4 Passive EPR Cable 0.5M HF
						X. ±0.50			UNIT 單位 MM
A	EXXXX-XXX	△ X 0	-	zhijun	2024/12/18	.X ±0.30 .XX ±0.20 ANG. ±5°00'	APPROVED 承認	DRAWN 製圖 zhijun 2024/12/18	SCALE 比例 1/1 SIZE 尺寸 A4
REV. 版本	ECN NO. 設變號碼	MARK 記號	REVISIONS 設變內容	SIGN 修改	DATE 日期				PART NO. 產品料號 U01-W158-00003 DOC. NO. 文件編號 CUT-W158-XXX
1		2	3	4	5	6	7	8	9 2/2